



Smooth Feed Out of All Rations

Loading Heights as Low as 95"

Low Horsepower Requirement

# Hay Pro

High Roughage Mixers

Specifically designed for today's dairyman or cattleman who demand the ability to blend two or more types of hay into a complete ration



Patent Pending

**Hay Pro Series** 1023-20 Truck and 533-16 Trailer shown  
400 to 1020 cu. ft. Truck, Trailer or Stationary

**ROTO-MIX LLC**

2205 East Wyatt Earp Blvd., P.O. Box 1724 Dodge City, Kansas 67801

Fax 620.225.6370 • [www.rotomix.com](http://www.rotomix.com) • [info@rotomix.com](mailto:info@rotomix.com)

**Phone 620.225.1142**




Adjustable height conveyor works equally well in bunks or on the floor in front of stanchions.



Easy access, single point latch doors on both truck and trailer models.



Front mounted hydrostatic pumps on truck models insure convenient maintenance.



Low profile weighbar type scale mount lowers loading height by 5 1/2". CT type loadcells are also available.

# Hay Pro

Patent Pending

**Blend 1, 2, or more types of hay as part of complete rations, or feed as a ration consisting of hay only**

- Lifts the ration as the ration is carried forward. This lifting action gives the Hay Pro the ability to evenly feed off all rations.
- Hay Pro rotor combines forward movement with lifting action for excellent mixing and unloading.



Hay Pro High Roughage Series Specifications	403-12	533-16	653-16	1023-20	
Weight w/Common Options	11,480	14,020	14,700	22,900	
Struck Level Capacity, Cubic Feet	400	530	650	1020	
Width, 3' Conveyor Up	94"	94"	94"	112"	
Conveyor Length Options	3 and 4'	3 and 4'	3 and 4'	3 and 4'	
Height, Trailer Standard Tires	95"	95"	108"	112"	
Height, Truck 38" Frame	N/A	N/A	N/A	128/133"	
Discharge Conveyor Width	36"	48"	48"	48"	
Bottom Thickness	1/4"	1/4"	1/4"	1/4"	
Stainless Bottom Liner (std)	12 ga.	12 ga.	12 ga.	10 ga.	
Upper Side Thickness	3/16"	3/16"	3/16"	1/4"	
Endsheet Thickness Lower	All Sizes—3/8" Front / 1/4" Rear				
Endsheet Thickness Upper	3/16"	3/16"	3/16"	1/4"	
Hay Pro Rotor Diameter	34"	34"	34"	42"	
Top Auger Diameter	24"	24"	24"	30"	
Minimum Horsepower	Truck	200	210	210	275
	Trailer	90	95	120	180
	Stationary	50	60	75	125

*All Models Available in Truck, Trailer or Stationary*

All Dimensions and Specification Are Subject To Change Without Notice

**You have to see it to believe it! Ask for a demonstration.**

*Distributed by:*

For additional information visit us at

[www.rotomix.com](http://www.rotomix.com)

