



Twin Vertical Feed Mixers

Flared Side, Twin Screw Design Advantages

Lower Loading Height

Smaller Diameter Tub
Bottom Reduces Torque

Larger Diameter Tub Top
Increase Capacity

More Knives & Flighting
to Process Hay Faster

Tapered Sides
For Improved Feed Flow

Optional End Extensions Prevent
Hay Spillage Without
Increasing Loading Height



AUTO-MIX Drive Advantages

Reduced Horsepower

Reduced Startup Torque

Faster, More Even Unloading

Improved Clean Out

Superior Hay Length Control

Circulation Pump Standard

Eliminates PTO Overload
Failures

Truck, Trailer, or Stationary



Made In The U.S.A. With Proven **ROTO-MIX** Quality!

ROTO-MIX, LLC
2205 E. Wyatt Earp
PO Box 1724
Dodge City, KS 67801



Phone (620) 225-1142
Fax (620) 225-6370
www.rotomix.com
info@rotomix.com

Unloading Method

choose from either
front corner chain
conveyor discharge

or

Low maintenance
left front side discharge
with twin magnets



Dimensions/Specifications

	1105	1355
Weight, trailer model * (less extensions)	17,100	17,900
Weight, truck model (less extensions)	15,500	16,000
Weight, 8" end-cap extensions	150	150
PTO speed trailer	1,000	1,000
Tires O.D., trailer*	42"	37"
Tires size, trailer*	11R x 22.5"	255R70 x 22.5"
Spout width, side discharge model	46"	46"
Conveyor width, conveyor models	40	40
Transmission speeds, trailer & stationary**	4	4
Screw speeds @ rated engine RPM	12 to 38	12 to 38
Loading height, Trailers*	114"	130"
Loading height, Trucks (40' Frame)	128"	144"
Maximum load with heavy compost (lbs.)	27,500	33,500
Mixing capacity (cubic yard)	1,100	1,350

** All ROTO-MIX trailer & stationary vertical mixers are equipped with remanufactured Allison Transmissions.



AUTO-MIX trailers and stationaries are equipped with a heavyduty rebuilt Allison transmission



AUTO-MIX trucks are furnished with a variable speed variable displacement hydrostatic system



Huge, open top allows Ingredients to be processed quickly. Twin screws and up to 18 knives insure quick, complete cutting and mixing

Optional rear auxilliary door allows unloading directly into commodity bay



Designed For Feeding Performance **ROTO-MIX**



All specifications are subject to change without notice

Sold and serviced in your area by:

Blank space for contact information.